

Artistic Skylights conform to and exceed test requirements of the following criteria:
AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on flat roofs only. Designed for mounting on 3"(75mm) or 4"(102mm) curbs with flashing (by others), The flexible design makes it easy to achieve larger daylight openings, while providing an excellent alternative as a lightweight assembly to traditional heavy glass systems.



| Project: | | Date: | |
|--------------------------------|-------------------------|-----------------|-------------|
| Model G-P-CU-CF-FF-VE | | | |
| Model # | Outside Curb Dimensions | Glazing Type | QTY |
| G-P-CU-CF-FF-VE CUST. | | | |
| G-P-CU-CF-FF-VE CUST. | | | |
| Glass Glazing Available | | | |
| Glass Glazing | Colour Code | Glass Glazing | Colour Code |
| Clear/Low-E | - Low-E | Clear/Laminated | - Lami. |
| Bronze/Low-E | - B/Low-E | Argon/Low-E | - Low-E/Arg |

Specifications:

Skylight shall be factory assembled Model No. _____ G-P-CU-CF-FF-VE as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of sealed dual tempered glass of clear low-E over clear. The skylight shall consist of corrosion resistant extruded aluminum curb frame, 6063-T5 alloy, with heliarc welded corners. The skylight curb frame shall have an extruded aluminum vinyl thermal break, with high capacity, sloped condensation gutter and drainage to exterior. The retaining cap frame shall be extruded, mill finish, 6063-T5 aluminum alloy with heliarc welded corners. Ridge shall consist of mill finish extruded aluminum channel and pressure plate of 6063-T5 alloy, with keyed in place Santoprene gaskets. Options include painted, anodized or powder coated finishes on aluminum.

