

## Venting (Electric) Glass Curb Mount Skylight (Sloped Roof)

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on all types of slope roofs. Designed for mounting on 1%" (38mm) curbs with flashing (by others), these units provide excellent performance in all geographic locations.

- Flashing kits available for asphalt shingle roofs
- Custom sizes are available upon request
- Custom applications available

Custom applications available					Charifications	
Model E-GV-PVCCM Available Sizes					Specifications: Skylight shall be factory assembled Model	
Model #	B x B Dimension			QTY	No. EV-G-PVCCM as manufactured by	
E-GV-PVCCM 2828	22¼" x 22¼" (565mm x	565mm)	, i y p o Qii	α	Artistic Skylight Domes Ltd. Vaughan, Ontario.	
E-GV-PVCCM 2836	22¼" x 30¼" (565mm x	768mm)			Glazing shall consist of sealed double tempered	
E-GV-PVCCM 2852	22½" x 46½" (565mm x	,			glass of clear Low-E over clear. The skylight	
E-GV-PVCCM 2860	22½" x 55" (565mm x			incorporates a heavy-duty corrosion resistant chain		
E-GV-PVCCM 2876	22½" x 69½" (565mm x 1765mm)				drive operating motor, pin pivot hinge system and removable insect screen. The skylight shall consist of a high-impact rigid extruded vinyl curb frame (superior in thermal conductivity to aluminum)	
E-GV-PVCCM 3636	30¼" x 30¼" (768mm x 768mm)					
E-GV-PVCCM 3642	30½" x 37" (768mm x 940mm) 30½" x 46½" (768mm x 1175mm) 30½" x 55" (768mm x 1397mm)					
E-GV-PVCCM 3652						
E-GV-PVCCM 3660						
E-GV-PVCCM 4242	37" x 37" (940mm x	940mm)			which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to the	
E-GV-PVCCM 4252	37" x 46½" (940mm x	1175mm)				
E-GV-PVCCM 5252	46¼" x 46¼" (1175mm)	( 1175mm)			exterior, a co-extruded rubber draft seal and a	
E-GV-PVCCM CUST.					white baked enamel extruded aluminum sash	
E-GV-PVCCM CUST.					frame, alloy 6063-T5. The retaining cap frame shall	
Glazing Available					be extruded, mill finish (optional baked enamel),	
Glazing Type	Colour Code	Glazing Type	g Type Colour Code		6063-T5 aluminum alloy with heliarc welded	
Clear/Low-E	Low-E	Clear/Laminated	Lami.		corners. Control options include wall mounted	
Bronze/Low-E	B/Low-E	Argon/Low-E	Low-E/Arg		switch and/or remote control with rain sensor.	
Project:				Architect:		
Contractor: Ap		Approved By:		·	Date:	

