

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on flat roofs, for mounting on curbs and flashing by others. Provides flexibility to obtain openings by joining two or more skylights in grid format.

Custom sizes are available upon request



Model G-FF-BUTTED Available Sizes

Model #	Centerline Dimensions	Glazing Type	QTY
G-FF-BUTTED 7272	70" x 35" (1778mm x 889mm)		
G-FF BUTTED 8080	78" x 39" (1981mm x 991mm)		
G-FF-BUTTED 9696	92½" x 46¼" (2350mm x 1175mm)		
	TBD x TBD (TBD x TBD)		
	TBD x TBD (TBD x TBD)		
G-FF-BUTTED CUST.			
G-FF-BUTTED CUST.			
G-FF-BUTTED CUST.			

Glazing Available			
Glazing Type	Colour Code	Glazing Type	Colour Code
Clear/Low-E	Low-E	Clear/Laminated	Lami.
Bronze/Low-E	B/Low-E	Argon/Low-E	Low-E/Arg

Project:	
Contractor:	Approved By:
Architect:	Date:

Specifications:

Skylight shall be factory assembled Model No. _____ G-FF-BUTTED as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed dual tempered glass of clear low-E over clear. The skylight shall consist of corrosion resistant extruded aluminum curb frame, 6063-T5 alloy, with heliarc welded corners. The skylight curb frame shall have an extruded rigid vinyl thermal break (to prevent thermal transfer to interior of building) which incorporates a high capacity, 5 degree sloped condensation gutter with drainage to exterior, and co-extruded rubber draft seal. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners.

