

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on flat roofs, for mounting on curbs and flashing by others. Provides flexibility to obtain longer openings by joining two or more skylights in linear length.

- Custom sizes are available upon request



Model FF-BUTTED Available Sizes			
Model #	Centerline Dimensions	Dome Colour	QTY
FF-BUTTED 3636	33 3/4" x 33 3/4" (845mm x 845mm)		
FF-BUTTED 4242	40" x 40" (1016mm x 1016mm)		
FF-BUTTED 5252	49 1/4" x 49 1/4" (1251mm x 1251mm)		
FF-BUTTED 6060	58" x 58" (1473mm x 1473mm)		
FF-BUTTED 7272	70" x 70" (1778mm x 1778mm)		
FF-BUTTED 9696	92 1/2" x 92 1/2" (2350mm x 2350mm)		
FF-BUTTED CUST.			
FF-BUTTED CUST.			

Dome Colours Available			
Dome Colour	Colour Code	Dome Colour	Colour Code
Clear	C	White	W
Bronze	B	Grey	G

Project:	
Contractor:	Approved By:
Architect:	Date:

Specifications:

Skylight shall be factory assembled Model No. _____ FF-BUTTED as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed double acrylic domes (or sealed triple domes) of clear, white, bronze, or grey. The skylight shall consist of corrosion resistant extruded aluminum curb frame, 6063-T5 alloy, with heliarc welded corners. The skylight curb frame shall have an extruded rigid vinyl thermal break (to prevent thermal transfer to interior of building) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to exterior, and co-extruded rubber bulb draft seal. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners. Mullions shall consist of 7" mill finish (optional baked enamel), extruded aluminum channel and pressure plate, 6063-T5 alloy, with resilient neoprene gaskets. Structural and intermediate supports are supplied by others.

