

Model V-PVCSR

Venting Dome Self Flashing Skylight

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights designed to be installed on shingled roofs with minimum 3:12 pitch. These skylights mount directly over roof opening and require no curbs or metal flashings.

- Underlayment and backpan required for proper installation.
- Custom sizes are available upon request



Model V-PVCSR Available Sizes								Specifications:	
Model #		ВxЕ	3 Dimensions	Dome Colour QTY			QTY	Skylight shall be factory assembled Model	
V-PVCSR 2828	22¼" x	(221/4"	(565mm x 565r	nm)				NoV-PVCSR as Manufactured by Artistic	
V-PVCSR 2836	22¼" x	30¼"	(565mm x 768r	imm)				Skylight Domes Ltd., Vaughan, Ontario. Glazing shall	
V-PVCSR 2852	22¼" x	46¼"	(565mm x 1175	ōmm)				consist of, sealed double acrylic domes (or sealed triple domes) of clear, white, bronze, or grey. The skylight incorporates a heavy duty corrosion resistant	
V-PVCSR 2860	22¼" x	55"	(565mm x 1397	7mm)					
V-PVCSR 2876	22¼" x	69½"	(565mm x 1765	ōmm)					
V-PVCSR 3636	30¼″ x	30¼"	(768mm x 768r	nm)				chain drive operating mechanism, pin pivot hinge	
V-PVCSR 3642	30¼" x	37"	(768mm x 940r	mm)				system and removable insect screen. The skylight	
V-PVCSR 3652	30¼" x	46¼"	(768mm x 1175	ōmm)				shall consist of rigid high-impact extruded vinyl base	
V-PVCSR 3660	30¼" x	30¼" x 55" (768mm x 1397mm)						 (superior in thermal conductivity to aluminum) which incorporates a high capacity, 18 degree sloped condensation gutter with drainage to exterior, co-extruded rubber draft seal, and 3" (76mm) mounting flange with a white baked enamel extruded 	
V-PVCSR 4242	37" x	37" x 37" (940mm x 940mm)							
V-PVCSR 4252	37" x	37" x 46¼" (940mm x 1175mm)							
V-PVCSR 5252	46¼″ x	46¼" x 46¼" (1175mm x 1175mm)							
V-PVCSR CUST.									
V-PVCSR CUST.								aluminum sash frame, alloy 6063-T5. The retaining	
Dome Colours Available							cap frame shall be extruded, mill finish (optional		
Dome Colou	ır	Col	our Code	Dor	Dome Colour		our Code	baked enamel), 6063-T5 aluminum alloy with heliarc	
Clear		С		White		W		welded corners. An optional telescoping pole-hook or electric motorized system are available.	
Bronze		В			Grey		G		
Project:								Architect:	
Contractor:				Approved By:				Date:	

