

Artistic Skylights conform to and exceed test requirements of the following criteria:
 AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights designed to be installed on shingled roofs with minimum 3:12 pitch. These skylights mount directly over roof opening and require no curbs or metal flashings.

- Underlayment and backpan required for proper installation.
- Custom sizes are available upon request



Model E-V-PVCSR Available Sizes

Model #	B x B Dimensions	Dome Colour	QTY
EV-PVCSR 2828	22 ¹ / ₄ " x 22 ¹ / ₄ " (565mm x 565mm)		
EV-PVCSR 2836	22 ¹ / ₄ " x 30 ¹ / ₄ " (565mm x 768mm)		
EV-PVCSR 2852	22 ¹ / ₄ " x 46 ¹ / ₄ " (565mm x 1175mm)		
EV-PVCSR 2860	22 ¹ / ₄ " x 55" (565mm x 1397mm)		
EV-PVCSR 2876	22 ¹ / ₄ " x 69 ¹ / ₂ " (565mm x 1765mm)		
EV-PVCSR 3636	30 ¹ / ₄ " x 30 ¹ / ₄ " (768mm x 768mm)		
EV-PVCSR 3642	30 ¹ / ₄ " x 37" (768mm x 940mm)		
EV-PVCSR 3652	30 ¹ / ₄ " x 46 ¹ / ₄ " (768mm x 1175mm)		
EV-PVCSR 3660	30 ¹ / ₄ " x 55" (768mm x 1397mm)		
EV-PVCSR 3676	30 ¹ / ₄ " x 69 ¹ / ₂ " (768mm x 1765mm)		
EV-PVCSR 4242	37" x 37" (940mm x 940mm)		
EV-PVCSR 4252	37" x 46 ¹ / ₄ " (940mm x 1175mm)		
EV-PVCSR 5252	46 ¹ / ₄ " x 46 ¹ / ₄ " (1175mm x 1175mm)		
EV-PVCSR CUST.			

Dome Colours Available

Dome Colour	Colour Code	Dome Colour	Colour Code
Clear	C	White	W
Bronze	B	Grey	G

Project:	Architect:
Contractor:	Approved By:
	Date:

Specifications:
 Skylight shall be factory assembled Model No. _____ EV-PVCSR as Manufactured by Artistic Skylight Domes Ltd., Vaughan, Ontario. Glazing shall consist of, sealed double acrylic domes (or sealed triple domes) of clear, white, bronze, or grey. The skylight incorporates a heavy duty corrosion resistant chain drive operating motor, pin pivot hinge system and removable insect screen. The skylight shall consist of rigid high-impact extruded vinyl base (superior in thermal conductivity to aluminum) which incorporates a high capacity, 18 degree sloped condensation gutter with drainage to exterior, co-extruded rubber draft seal, and 3" (76mm) mounting flange with a white baked enamel extruded aluminum sash frame, alloy 6063-T5. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners. Control options include wall mounted switch and/or remote control with rain sensor.

