

Artistic Skylights conform to and exceed test requirements of the following criteria:  
 AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights designed to be installed on shingled roofs with minimum 3:12 pitch. These skylight mount directly over roof opening and require no curbs or metal flashings.

- Underlayment required for proper installation
- Custom sizes are available upon request



### Model G-SR Available Sizes

Model #	B x B Dimensions	Glazing Type	QTY
G-SR 2020	14 1/4" x 14 1/4" (362mm x 362mm)		
G-SR 2052	14 1/4" x 46 1/4" (362mm x 1175mm)		
G-SR 2828	22 1/4" x 22 1/4" (565mm x 565mm)		
G-SR 2836	22 1/4" x 30 1/4" (565mm x 768mm)		
G-SR 2852	22 1/4" x 46 1/4" (565mm x 1175mm)		
G-SR 2860	22 1/4" x 55" (565mm x 1397mm)		
G-SR 2876	22 1/4" x 69 1/2" (565mm x 1765mm)		
G-SR 2896	22 1/4" x 89 1/2" (565mm x 2273mm)		
G-SR 3636	30 1/4" x 30 1/4" (768mm x 768mm)		
G-SR 3642	30 1/4" x 37" (768mm x 940mm)		
G-SR 3652	30 1/4" x 46 1/4" (768mm x 1175mm)		
G-SR 3660	30 1/4" x 55" (768mm x 1397mm)		
G-SR 3676	30 1/4" x 69 1/2" (768mm x 1765mm)		
G-SR 3696	30 1/4" x 89 1/2" (768mm x 2273mm)		
G-SR 4242	37" x 37" (940mm x 940mm)		
G-SR 4252	37" x 46 1/4" (940mm x 1175mm)		
G-SR 4280	37" x 75" (940mm x 1905mm)		
G-SR 5252	46 1/4" x 46 1/4" (1175mm x 1175mm)		
G-SR 5260	46 1/4" x 55" (1175mm x 1397mm)		
G-SR 5276	46 1/4" x 69 1/2" (1175mm x 1765mm)		
G-SR CUST.			
G-SR CUST.			

### Specifications:

Skylight shall be factory assembled Model No. \_\_\_\_\_ G-SR as Manufactured by Artistic Skylight Domes Ltd., Vaughan, Ontario. Glazing shall consist of, sealed dual tempered glass of clear low-E over clear. The skylight shall consist of corrosion resistant extruded aluminum base frame, 6063-T5 alloy, and 3" aluminum mounting flange with heliarc welded corners. The skylight base frame shall have 2" thermal insulation and an extruded rigid vinyl thermal break (to prevent thermal transfer to interior of building) which incorporates a high capacity, 8 degree sloped condensation gutter with drainage to exterior, and co extruded rubber draft seal. Retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners.

### Glazing Available

Glazing Type	Colour Code	Glazing Type	Colour Code
Clear/Low-E	Low-E	Clear/Laminated	Lami.
Bronze/Low-E	B/Low-E	Argon/Low-E	Low-E/Arg

Project:	Architect:
Contractor:	Approved By:
	Date:

