

Artistic Skylights conform to and exceed test requirements of the following criteria:  
AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights designed to be installed on shingled roofs with minimum 3:12 pitch. These skylights mount directly over roof opening and require no curbs or metal flashings.

- Underlayment and backpan required for proper installation.
- Custom sizes are available upon request



Model E-SP-GV-PVCSR Available Sizes			
Model #	B x B Dimensions	Glazing Type	QTY
E-SP-GV-PVCSR 2828	22 $\frac{1}{4}$ " x 22 $\frac{1}{4}$ " (565mm x 565mm)		
E-SP-GV-PVCSR 2836	22 $\frac{1}{4}$ " x 30 $\frac{1}{4}$ " (565mm x 768mm)		
E-SP-GV-PVCSR 2852	22 $\frac{1}{4}$ " x 46 $\frac{1}{4}$ " (565mm x 1175mm)		
E-SP-GV-PVCSR 2860	22 $\frac{1}{4}$ " x 55" (565mm x 1397mm)		
E-SP-GV-PVCSR 2876	22 $\frac{1}{4}$ " x 69 $\frac{1}{2}$ " (565mm x 1765mm)		
E-SP-GV-PVCSR 3636	30 $\frac{1}{4}$ " x 30 $\frac{1}{4}$ " (768mm x 768mm)		
E-SP-GV-PVCSR 3642	30 $\frac{1}{4}$ " x 37" (768mm x 940mm)		
E-SP-GV-PVCSR 3652	30 $\frac{1}{4}$ " x 46 $\frac{1}{4}$ " (768mm x 1175mm)		
E-SP-GV-PVCSR3660	30 $\frac{1}{4}$ " x 55" (768mm x 1397mm)		
E-SP-GV-PVCSR 4242	37" x 37" (940mm x 940mm)		
E-SP-GV-PVCSR 4252	37" x 46 $\frac{1}{4}$ " (940mm x 1175mm)		
E-SP-GV-PVCSR 5252	46 $\frac{1}{4}$ " x 46 $\frac{1}{4}$ " (1175mm x 1175mm)		
E-SP-GV-PVCSR CUST.			
E-SP-GV-PVCSR CUST.			
Glazing Available			
Glazing Type	Colour Code	Glazing Type	Colour Code
Clear/Low-E	Low-E	Clear/Laminated	Lami.
Bronze/Low-E	B/Low-E	Argon/Low-E	Low-E/Arg
Project:		Architect:	
Contractor:		Approved By:	
		Date:	

**Specifications:**

Skylight shall be factory assembled Model No. \_\_\_\_\_ E-SP-GV-PVCSR as Manufactured by Artistic Skylight Domes Ltd., Vaughan, Ontario. Glazing shall consist of, sealed dual tempered glass of clear low-E over clear. The skylight incorporates a heavy duty corrosion resistant chain drive operating motor, pin pivot hinge system and removable insect screen. The skylight shall consist of rigid high-impact extruded vinyl base (superior in thermal conductivity to aluminum) which incorporates a high capacity, 18 degree sloped condensation gutter with drainage to exterior, co-extruded rubber draft seal, and 3" (76mm) mounting flange with a white baked enamel extruded aluminum sash frame, alloy 6063-T5. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners. Control options include wall mounted switch and/or remote control with rain sensor.

