

Artistic Skylights conform to and exceed test requirements of the following criteria:
 AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights designed to be installed on shingled roofs with minimum 3:12 pitch. These skylights mount directly over roof opening and require no curbs or metal flashings.

- Underlayment and backpan required for proper installation.
- Custom sizes are available upon request



Model PVCSR Available Sizes

Model #	B x B Dimensions	Dome Colour	QTY
PVCSR 2020	14¼" x 14¼" (362mm x 362mm)		
PVCSR 2052	14¼" x 46¼" (362mm x 1175mm)		
PVCSR 2828	22¼" x 22¼" (565mm x 565mm)		
PVCSR 2836	22¼" x 30¼" (565mm x 768mm)		
PVCSR 2852	22¼" x 46¼" (565mm x 1175mm)		
PVCSR 2860	22¼" x 55" (565mm x 1397mm)		
PVCSR 2876	22¼" x 69½" (565mm x 1765mm)		
PVCSR 2896	22¼" x 89½" (565mm x 2273mm)		
PVCSR 3636	30¼" x 30¼" (768mm x 768mm)		
PVCSR 3642	30¼" x 37" (768mm x 940mm)		
PVCSR 3652	30¼" x 46¼" (768mm x 1175mm)		
PVCSR 3660	30¼" x 55" (768mm x 1397mm)		
PVCSR 3676	30¼" x 69½" (768mm x 1765mm)		
PVCSR 3696	30¼" x 89½" (768mm x 2273mm)		
PVCSR 4242	37" x 37" (940mm x 940mm)		
PVCSR 4252	37" x 46¼" (940mm x 1175mm)		
PVCSR 4280	37" x 75" (940mm x 1905mm)		
PVCSR 5252	46¼" x 46¼" (1175mm x 1175mm)		
PVCSR 5260	46¼" x 55" (1175mm x 1397mm)		
PVCSR 5276	46¼" x 69½" (1175mm x 1765mm)		
PVCSR 5280	46¼" x 75" (1175mm x 1905mm)		
PVCSR 5296	46¼" x 89½" (1175mm x 2273mm)		
PVCSR 6060	55" x 55" (1397mm x 1397mm)		
PVCSR 6076	55" x 69½" (1397mm x 1765mm)		
PVCSR 6096	55" x 89½" (1397mm x 2273mm)		
PVCSR 7272	67" x 67" (1702mm x 1702mm)		
PVCSR 7296	67" x 89½" (1702mm x 2273mm)		
PVCSR CUST.			
PVCSR CUST.			

Specifications:

Skylight shall be factory assembled Model No. _____ PVCSR as Manufactured by Artistic Skylight Domes Ltd., Vaughan, Ontario. Glazing shall consist of, sealed double acrylic domes (or sealed triple domes) of clear, white, bronze, or grey. The skylight shall consist of rigid high-impact extruded vinyl base (superior in thermal conductivity to aluminum) which incorporates a high capacity, 18 degree sloped condensation gutter with drainage to exterior, co-extruded rubber draft seal, and 3" (76mm) mounting flange. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners.

Project:
Contractor:
Architect:
Approved By:
Date:

Dome Colours Available

Dome Colour	Colour Code	Dome Colour	Colour Code
Clear	C	White	W
Bronze	B	Grey	G

