

Artistic Skylights conform to and exceed test requirements of the following criteria:
 AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard /
 Specification for windows, doors and skylights)

Skylights are suitable for use on all types of slope roofs. Designed for mounting on 3" (76mm) curbs with flashing (by others), these units provide excellent performance in all geographic locations.

- Flashing kits available for asphalt shingle roofs
- Custom sizes are available upon request
- Custom applications available



Model PVCCM Available Sizes

Model #	Outside Curb Dimensions	Dome Colour	QTY
PVCCM 2020	17¼" x 17¼" (435mm x 435mm)		
PVCCM 2052	17¼" x 49¼" (435mm x 1251mm)		
PVCCM 2828	25¼" x 25¼" (641mm x 641mm)		
PVCCM 2836	25¼" x 33¼" (641mm x 845mm)		
PVCCM 2852	25¼" x 49¼" (641mm x 1251mm)		
PVCCM 2860	25¼" x 58" (641mm x 1473mm)		
PVCCM 2876	25¼" x 72½" (641mm x 1842mm)		
PVCCM 2896	25¼" x 92½" (641mm x 2349mm)		
PVCCM 3636	33¼" x 33¼" (845mm x 845mm)		
PVCCM 3642	33¼" x 40" (845mm x 1016mm)		
PVCCM 3652	33¼" x 49¼" (845mm x 1251mm)		
PVCCM 3660	33¼" x 58" (845mm x 1473mm)		
PVCCM 3676	33¼" x 72½" (845mm x 1842mm)		
PVCCM 3696	33¼" x 92½" (845mm x 2349mm)		
PVCCM 4242	40" x 40" (1016mm x 1016mm)		
PVCCM 4252	40" x 49¼" (1016mm x 1251mm)		
PVCCM 4280	40" x 78" (1016mm x 1981mm)		
PVCCM 5252	49¼" x 49¼" (1251mm x 1251mm)		
PVCCM 5260	49¼" x 58" (1251mm x 1473mm)		
PVCCM 5276	49¼" x 72½" (1251mm x 1842mm)		
PVCCM 5280	49¼" x 78" (1251mm x 1981mm)		
PVCCM 5296	49¼" x 92½" (1251mm x 2349mm)		
PVCCM 6060	58" x 58" (1473mm x 1473mm)		
PVCCM 6076	58" x 72½" (1473mm x 1842mm)		
PVCCM 6096	58" x 92½" (1473mm x 2349mm)		
PVCCM 7272	70" x 70" (1778mm x 1778mm)		
PVCCM 7296	70" x 92½" (1778mm x 2349mm)		
PVCCM CUST.			
PVCCM CUST.			

Specifications:

Skylight shall be factory assembled Model No. _____ PVCCM as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed double acrylic domes (or sealed triple domes) of clear, white, bronze, or grey. The skylight shall consist of rigid high-impact extruded vinyl curb frame (superior in thermal conductivity to aluminum) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to exterior, co-extruded rubber draft seal. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners.

Project:
Contractor:
Architect:
Approved By:
Date:

Dome Colours Available

Dome Colour	Colour Code	Dome Colour	Colour Code
Clear	C	White	W
Bronze	B	Grey	G

