

Artistic Skylights conform to and exceed test requirements of the following criteria:  
 AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on all types of slope roofs. Designed for mounting on 1/2" (38mm) curbs with flashing (by others), these units provide excellent performance in all geographic locations.

- Flashing kits available for asphalt shingle roofs
- Custom sizes are available upon request
- Custom applications available



### Model T-PVCCM Available Sizes

Model #	B x B Dimensions	Dome Colour	QTY
T-PVCCM 2020	14 1/4" x 14 1/4" (362mm x 362mm)		
T-PVCCM 2052	14 1/4" x 46 1/4" (362mm x 1175mm)		
T-PVCCM 2828	22 1/4" x 22 1/4" (565mm x 565mm)		
T-PVCCM 2836	22 1/4" x 30 1/4" (565mm x 768mm)		
T-PVCCM 2852	22 1/4" x 46 1/4" (565mm x 1175mm)		
T-PVCCM 2860	22 1/4" x 55" (565mm x 1397mm)		
T-PVCCM 2876	22 1/4" x 69 1/2" (565mm x 1765mm)		
T-PVCCM 2896	22 1/4" x 89 1/2" (565mm x 2273mm)		
T-PVCCM 3636	30 1/4" x 30 1/4" (768mm x 768mm)		
T-PVCCM 3642	30 1/4" x 37" (768mm x 940mm)		
T-PVCCM 3652	30 1/4" x 46 1/4" (768mm x 1175mm)		
T-PVCCM 3660	30 1/4" x 55" (768mm x 1397mm)		
T-PVCCM 3676	30 1/4" x 69 1/2" (768mm x 1765mm)		
T-PVCCM 3696	30 1/4" x 89 1/2" (768mm x 2273mm)		
T-PVCCM 4242	37" x 37" (940mm x 940mm)		
T-PVCCM 4252	37" x 46 1/4" (940mm x 1175mm)		
T-PVCCM 4280	37" x 75" (940mm x 1905mm)		
T-PVCCM 5252	46 1/4" x 46 1/4" (1175mm x 1175mm)		
T-PVCCM 5260	46 1/4" x 55" (1175mm x 1397mm)		
T-PVCCM 5276	46 1/4" x 69 1/2" (1175mm x 1765mm)		
T-PVCCM 5280	46 1/4" x 75" (1175mm x 1905mm)		
T-PVCCM 5296	46 1/4" x 89 1/2" (1175mm x 2273mm)		
T-PVCCM 6060	55" x 55" (1397mm x 1397mm)		
T-PVCCM 6076	55" x 69 1/2" (1397mm x 1765mm)		
T-PVCCM 6096	55" x 89 1/2" (1397mm x 2273mm)		
T-PVCCM 7272	67" x 67" (1702mm x 1702mm)		
T-PVCCM 7296	67" x 89 1/2" (1702mm x 2273mm)		
T-PVCCM CUST.			
T-PVCCM CUST.			

### Specifications:

Skylight shall be factory assembled Model No. \_\_\_\_\_ T-PVCCM as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed triple acrylic domes of clear, white, bronze, or grey. The skylight shall consist of rigid high-impact extruded vinyl curb frame (superior in thermal conductivity to aluminum) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to the exterior, a co-extruded rubber draft seal. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners.

Project:
Contractor:
Architect:
Approved By:
Date:

### Dome Colours Available

Dome Colour	Colour Code	Dome Colour	Colour Code
Clear	C	White	W
Bronze	B	Grey	G

