

Venting Glass Curb Mount Skylight (Sloped Roof)


Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on all types of slope roofs. Designed for mounting on 1½" (38mm) curbs with flashing (by others), these units provide excellent performance in all geographic locations

- Flashing kits available for asphalt shingle roofs
- Custom sizes are available upon request
- Custom applications available

Model GV-PVCCM Available Sizes								
Model #	B x B Dimensions			S	Glazing ⁻	Туре	Flashing Kit QTY	QTY
GV-PVCCM 2828	22	1/4" x 221/4"	(565mm x 56	5mm)				
GV-PVCCM 2836	22	¼" x 30¼"	(565mm x 76	8mm)				
GV-PVCCM 2852	22	1/4" x 461/4"	(565mm x 11	,				
GV-PVCCM 2860	22	¼" x 55"	(565mm x 13					
GV-PVCCM 2876	22	1/4" x 691/2"	(565mm x 17	65mm)				
GV-PVCCM 3636	30	30½" x 30½" (768mm x 768mm)						
GV-PVCCM 3642	30	¼" x 37"	(768mm x 94	0mm)				
GV-PVCCM 3652	30	1/4" x 461/4"	(768mm x 11					
GV-PVCCM 3660	30	¼" x 55"	(768mm x 13	97mm)				
GV-PVCCM 4242	37	" x 37"	(940mm x 94	0mm)				
GV-PVCCM 4252	37	37" x 46¼" (940mm x 1175mm)						
GV-PVCCM 5252	46	46½" x 46½" (1175mm x 1175mm)						
GV-PVCCM CUST.								
GV-PVCCM CUST.								
Glazing Available								
Glazing Type Colo		ır Code	Glaz	zing Type	Colour Code			
Clear/Low-E Lo		ow-E Clea		Laminated	Lami.			
Bronze/Low-E		B/Low-E		Argon/Low-E		Low-E/Arg		
Project:	·							

Approved By:



Specifications:

Architect:

Date:

Skylight shall be factory assembled Model GV-PVCCM as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of sealed double tempered glass of clear Low-E over clear. The skylight incorporates a heavy-duty corrosion resistant chain drive operating mechanism, pin pivot hinge system and removable insect screen. The skylight shall consist of a high-impact rigid extruded vinyl curb frame (superior in thermal conductivity to aluminum) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to the exterior, a co-extruded rubber draft seal and a white baked enamel extruded aluminum sash frame, alloy 6063-T5. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners. An optional telescoping pole-hook or electric motorized system are available.

INSULATED TE BUTYL RETAINER FRAME SEA EXTRUDED ALUMINUM RETAINER CAP FRAME SETTING BLOCK #8 S.S ASSEMBLY SCREW EXTRUDED ALUMINUM SASH FRAME RIGID BULB (FLEXIBLE PVC-UV STABLE) CONDENSATION GUTTER - RIGID VINYL CURB MOUNT - FRAME CURB - ROOF MEMBRANE - METAL FLASHING -	REMOVABLE INSECT SCREEN CHAIN DRIVE OPERATING MECHANISM B x B CURB OPENING DIMENSION
	CURB OPENING DIMENSION

Contractor: