

## Venting (Dual Electric) Dome Curb Mount Skylight with Prefabricated Aluminum Curb

Artistic Skylights conform to and exceed test requirements of the following criteria:  
AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on all types of flat roofs. These units provide excellent performance in all geographic locations.



Model E-V-CL (TQ) Available Sizes			
Model #	B x B Dimensions	Dome Colour	QTY
E-V-CL (TQ) 2896	22¼" X 89½" (565mm X 2273mm)		
E-V-CL (TQ) 3696	30¼" X 89½" (768mm X 2273mm)		
E-V-CL (TQ) 4280	22¼" X 75" (940mm X 1905mm)		
E-V-CL (TQ) 5276	46¼" X 69½" (1175mm X 1765mm)		
E-V-CL (TQ) 5280	46¼" X 75" (1175mm X 1905)		
E-V-CL (TQ) 5296	46¼" X 89½" (1175mm X 2273mm)		
E-V-CL (TQ) 6076	55" X 69½" (1397mm X 1765)		
E-V-CL (TQ) 6096	55" X 89½" (1397mm X 2273mm)		

  

Dome Colours Available			
Dome Colour	Colour Code	Dome Colour	Colour Code
Clear	C	White	W
Bronze	B		

  

Project:	
Contractor:	Approved By:
Architect:	Date:

Specifications:  
Skylight shall be factory assembled Model No. \_\_\_\_\_ E-V-CL (TQ) as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed double acrylic domes (or sealed triple domes) of clear, white, or bronze. The skylight incorporates a heavy-duty corrosion resistant dual chain drive operating mechanism, pin pivot hinge system (hinged on long side) and removable insect screen. The skylight shall consist of rigid high-impact extruded vinyl curb frame (superior in thermal conductivity to aluminum) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to exterior, co-extruded rubber draft seal and a white baked enamel extruded aluminum sash frame, all 6063-T5. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners. Control option include wall mounted switch. Curb shall be, 9" high (optional 12") mill finish aluminum, 2 piece construction of .050 outer wall and .050 inner wall, with 1½" thick insulation and 2" aluminum mounting flange.



RAIN SENSOR



WALL SWITCH



CONTROL PANEL



ELECTRIC DUAL CHAIN MOTOR

NOTE:  
INSTALLATION AND WIRING OF THESE COMPONENTS (BY CERTIFIED ELECTRICIAN)  
CONTROL PANEL (CRM3)  
RAIN SENSOR (40690A)  
WALL SWITCH (5W5657-2W)

