

Circular Dome Curb Mount Skylight with Aluminum Curb (Flat Roof)

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights designed to be installed on flat roofs. These skylights mount directly over roof opening and come complete with prefabricated, insulated aluminum curbs.

- Custom sizes are available upon request



Model C Available Sizes

Model #	B Diameter	Dome Colour	QTY
C 28	22½" (572mm)		
C 36	30½" (775mm)		
C 42	37" (940mm)		
C 48	43" (1092mm)		
C 52	46½" (1181mm)		
C 60	55" (1397mm)		
C 72	67" (1702mm)		
C 80	75" (1905mm)		
C 96	89½" (2273mm)		
C CUST.			

Dome Colours Available

Dome Colour	Colour Code	Dome Colour	Colour Code
Clear	C	White	W
Bronze	B	Grey	G

Project:	Architect:
Contractor:	Approved By:
	Date:

Specifications:

Skylight shall be factory assembled Model No. C _____ as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed double acrylic domes (or sealed triple domes) of clear, white, bronze, or grey. skylight shall consist of aluminum curb frame with thermal break and sloped condensation gutter with drainage to exterior. Retaining cap frame shall be mill finish, 6063-T5 aluminum alloy. Curb shall be 9" high (optional 12") mill finish aluminum, 2 piece construction of .050 outer wall and .050 inner wall, with 2" thick fiberglass insulation and 3" aluminum mounting flange.

