

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Circular skylights designed to be installed vertically in wall. These skylights mount directly into wall opening.

- Custom sizes are available upon request



Model CWM Available Sizes				
Model #	Opening Diameter	Frame Diameter	Dome Colour	QTY
CWM 28	30" (762 mm)	29 1/4" (743 mm)		
CWM 36	38" (965 mm)	37 1/4" (946 mm)		
CWM 42	44 1/2" (1130 mm)	43 3/4" (1111 mm)		
CWM 52	54" (1372 mm)	53 1/4" (1352 mm)		
CWM 60	62 1/2" (1588 mm)	61 1/4" (1568 mm)		
CWM 72	74 1/2" (1892 mm)	73 3/4" (1873 mm)		
CWM 80	82 1/2" (2096 mm)	81 1/4" (2076 mm)		
CWM 96	97" (2464 mm)	96 1/4" (2445 mm)		
CWM CUST.				
CWM CUST.				

Project:
Contractor:
Architect:
Approved By:
Date:

Dome Colours Available			
Dome Colour	Colour Code	Dome Colour	Colour Code
Clear	C	White	W
Bronze	B	Grey	G

Specifications:

Skylight shall be factory assembled Model No. _____ CWM as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed double acrylic domes (or sealed triple domes) of clear, white, bronze, or grey. Skylight shall consist of double aluminum frame with thermal break and condensation drainage. Frame shall be mill finish (optional baked enamel), 6063-T5 aluminum alloy.

