

Circular Glass Curb Mount Skylight (Flat and Sloped Roofs)

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights designed to be installed on flat roofs (with sloped curb) or sloped roofs. These skylights are designed for installation on 3" curbs with flashings by others

- Custom sizes and/or custom applications are available upon request

Model G-CCM Available Sizes				
Model #	B Diameter	Overall Curb Diameter	Glazing Type	QTY
G-CCM 28	20½" (521mm)	26½" (673mm)		
G-CCM 36	28½" (724mm)	34½" (876mm)		
G-CCM 42	35" (889mm)	41" (1041mm)		
G-CCM 52	44½" (1130mm)	50½" (1283mm)		
G-CCM 60	53" (1346mm)	59" (1499mm)		
G-CCM 72	65" (1651mm)	71" (1803mm)		
G-CCM 80	73" (1854mm)	79" (2007mm)		
G-CCM 96	87½" (2223mm)	93½" (2375mm)		
G-CCM CUST.				
G-CCM CUST.				

Specifications:

Skylight shall be factory assembled Model No. _____ G-CCM as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed dual tempered glass of clear, bronze, or grey. Skylight shall consist of aluminum curb frame with thermal break and sloped condensation gutter with drainage to exterior. Retaining cap frame shall be mill finish, 6063-T5 aluminum alloy.

Glazing Available				Architect:
Glazing Type	Colour Code	Glazing Type	Colour Code	
Clear	C	Grey	G	Date:
Bronze	B			Distributor:
Project:				
Contractor:		Approved By:		

