

Artistic Skylights conform to and exceed test requirements of the following criteria:
AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights are suitable for use on all types of slope roofs. Designed for mounting on 1½" (38mm) curbs with flashing (by others), these units provide excellent performance in all geographic locations.

- Flashing kits available for asphalt shingle roofs
- Custom sizes are available upon request
- Custom applications available



Model P-PVCCM Available Sizes			
Model #	B x B Dimensions	Pyramid Colour	QTY
P-PVCCM 2852	22¼" x 46¼" (565mm x 1175mm)		
P-PVCCM 3636	30¼" x 30¼" (768mm x 768mm)		
P-PVCCM 3652	30¼" x 46¼" (768mm x 1175mm)		
P-PVCCM 3676	30¼" x 69½" (768mm x 1765mm)		
P-PVCCM 4242	37" x 37" (940mm x 940mm)		
P-PVCCM 5252	46¼" x 46¼" (1175mm x 1175mm)		
P-PVCCM 6060	55" x 55" (1397mm x 1397mm)		
P-PVCCM 7272	67" x 67" (1702mm x 1702mm)		
P-PVCCM CUST.			
P-PVCCM CUST.			

Pyramid Colours Available			
Pyramid Colour	Colour Code	Pyramid Colour	Colour Code
Clear	C	White	W
Bronze	B	Grey	G

Specifications:
Skylight shall be factory assembled Model No. _____ P-PVCCM as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed double acrylic pyramids (or sealed triple pyramids) of clear, white, bronze, or grey. The skylight shall consist of rigid high-impact extruded vinyl curb frame (superior in thermal conductivity to aluminum) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to exterior, co-extruded rubber draft seal. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners.

Project:	Architect:
Contractor:	Approved By:
	Date:

