

Prefabricated Aluminum Curb with Fixed Glass Skylight

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylight designed to be installed on flat roofs. These skylights come complete with insulated aluminum curb and mount directly over roof opening.

· Custom sizes are available upon request



Actual product may not be exactly as shown

Model G-CL Available Sizes						Specifications:
Model #		B x B Dimensions	Glazing T	ype Flashing Kit	QTY	Skylight shall be factory assembled Model
G-CL 2828 22/4 G-CL 2836 22/4 G-CL 2852 22/4 G-CL 2860 22/4 G-CL 2876 22/4 G-CL 2896 22/4 G-CL 3636 30/4 G-CL 3642 30/4 G-CL 3662 30/4 G-CL 3660 30/4 G-CL 3676 30/4 G-CL 3696 30/4 G-CL 3696 30/4 G-CL 4242 37" G-CL 4252 37" G-CL 4280 37"	" X 22½" " X 30½" " X 46½" " X 55" " X 89½" " X 30½" " X 37" " X 46½" " X 55" " X 46½" " X 55" " X 46½" " X 77" " X 46½" " X 45½" " X 45½" " X 45½" " X 45½"	(565mm x 565mm) (565mm x 768mm) (565mm x 1175mm) (565mm x 1795mm) (565mm x 1795mm) (565mm x 2273mm) (768mm x 768mm) (768mm x 940mm) (768mm x 1175mm) (768mm x 12273mm) (768mm x 12273mm) (940mm x 940mm) (940mm x 1175mm) (940mm x 1905mm)		ype way/n		No. G-CL as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed dual tempered glass of clear Low-E over clear. The skylight shall consist of a rigid high-impact extruded vinyl curb frame (superior in thermal conductivity to aluminum) which incorporates a high capacity, 10 degree sloped condensation gutter with drainage to the exterior, and a co-extruded rubber draft seal. The retaining cap frame shall be of extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy (0.063" thick), with heliarc welded corners. Curb shall be, 9" high (optional 12") mill finish aluminum, with a nominal 5 degree slope, 2 piece construction of .050 outer wall and .050 inner wall, with 1½" thick insulation and 2" aluminum mounting flange.
G-CL 5260 46¼ G-CL 5276 46¼ G-CL 5280 46¼ G-CL 5296 46¼ G-CL 6060 55" G-CL 6076 55" G-CL CUST.	x 55" x 69½" x 75" x 89½" x 55" x 69½"	(1175mm x 1397mr (1175mm x 1397mr (1175mm x 1905mr (1175mm x 2973mr (1397mm x 1397mr (1397mm x 1765mr	n) n) n) n)			Contractor: Architect:
G-CL CUST.						Approved By:
Glazing Available						
Glazing Type)	Colour Code	Glazing Type	Colour Code	Э	
Clear/Low-E		Low-E	Clear/Laminated	Lami.		Date:
Bronze/Low-E	=	B/Low-E	Argon/Low-E	Low-E/Arg		

