



## Circular Dome Curb Mount Skylight with Aluminum Curb (Sloped Roof)

Artistic Skylights conform to and exceed test requirements of the following criteria: AAMA/WDMA/CSA 101/I.S.2/A440-17 (NAFS - North American Fenestration Standard / Specification for windows, doors and skylights)

Skylights designed to be installed on flat and sloped roofs. These skylights mount directly over roof opening and come complete with prefabricated, insulated aluminum curbs.

## Custom sizes are available upon request

		' '					
Model C Available Sizes						Act	
Model #	B Dia	ameter	Dome Colour		QTY	Specifications:	
C 28 C 36 C 42 C 48 C 52 C 60 C 72 C 80 C 96 C-CUST.	30½" (775n 37" (940n 43" (1092 46½" (1181 55" (1397 67" (1702 75" (1905	30½" (775mm) 37" (940mm) 43" (1092mm) 46½" (1181mm) 55" (1397mm) 67" (1702mm) 75" (1905mm)			Skylight shall be factory a C as manufacture Domes Ltd. Vaughan, Ontario of, sealed double acrylic domes) of clear, white or bror Skylight shall consist of alunthermal break and sloped codrainage to exterior. Retaining mill finish, 6063-T6 aluminum		
Dome Colours Available						high mill finish aluminum, 2 .050 outer wall and .050 in	
Dome Colour	Colour Code	Dome Colour	Colour Code	Dome Colour	Colour Code	fiberglass insulation and 4	
Clear	С	Bronze	В	White	W	flange.	
Project:						Architect:	
Contractor:			Approved By:			Date:	



ctual product may not be exactly as shown

assembled Model No. red by Artistic Skylight rio. Glazing shall consist domes (or sealed triple

uminum curb frame with condensation gutter with ning cap frame shall be m alloy. Curb shall be 5" 2 piece construction of inner wall, with 2" thick 4" aluminum mounting

SEALED DOUBLE ACRYLIC DOME SILICONE SEAL VINYL THERMAL EXTRUDED ALUMINUM **BREAK RETAINER FRAME** POP RIVET UVHB HIGH BOND ACRYLIC FOAM GLAZING TAPE **INSULATION** CONTINUOUS DRAFT SEAL #12 S.S. ASSEMBLY FASTENER **EXTRUDED ALUMINUM CURB FRAME ROOF MEMBRANE AND** FLASHING (BY OTHERS) **SHINGLES** STITCH WELD 4" EXTERIOR ROOF FLANGE